



# Vibe+

ALPHANUMERIC PAGER

## MORE READABLE, STRONGER, & LONGER LASTING

Introducing the all new and improved Vibe+ Alphanumeric Pager..

### AVAILABLE NOW

Introducing the all-new Vibe+ Alphanumeric Pager—redesigned from the ground up and packed with powerful enhancements to elevate team communication like never before.



**Inform & Notify  
Staff Faster**



**Optimize  
Your Labor**



**Shorten  
Response Time**

### NEW FEATURES & IMPROVEMENTS:

- **NEW Larger, Full-Color screen with improved readability**
  - New back-lit, full color display
  - Scrolling messages with large, readable text
- **NEW Lithium-ion Battery for longer charge life**
- **NEW Charge Status Light**
- **Reformulated plastic case and clip for improved durability**
- **Full text based messaging for detailed communication**



## VIBE+ ALPHA PAGER SPECS



- Dimensions: 3" x 2 1/4" x 3/4"
- Weight: 2.25 oz
- Shock Absorbing Bumper
- Rechargeable 3.7 V Lithium-ion Battery
- 1 1/2" x 1 1/8" Large Color LCD display
- 3 Button User Interface
- Plastic clip or lanyard carry option
- Heartbeat Active LED
- Vibe, Beep, & Vibe Beep Notifications

### Charger

- 5 Slot smart charger, expandable to 15
- Full charge time - 4 Hours
- LED color charging indication



**RESEARCH.  
LEARN.  
SHOP.**

## COMPATIBLE LRS TRANSMITTERS



### LRS Connect Transmitter

- Integrates with LRS Next for the ultimate wait list, paging, and messaging platform
- Easy-to-Read, back lit display
- Selectable paging modes
- Anti-theft feature
- All locate feature
- Tracking Mode – keeps paging until page is cleared
- Range test mode
- Range extender mode
- Operates on 110V or 220V
- Footprint: 4" x 8"



### Pronto 1 & 6 Button Transmitter

- Versatile push for service transmitter
- Each button can be preprogrammed to send unique messages or the same message
- Notify multiple people with a simple button press
- Ideal for unattended areas or push for service applications



### LRS Interface Transmitter

- Integrates with 3rd party software and platforms to provide alphanumeric messaging
- Standard DE-9 (e.g. RS-232C) connector
- Operates on 110V or 220V
- Dimensions: 9.5"w x 4"h x 4.5"d
- Weight: 0.7 lbs

